PowerRack 1000™


RACKING SOLUTION


powerfield

PowerField Energy's PowerRack PV solar ground mount system is a revolutionary solution for low-cost low-impact versatile applications. This ballasted system requires no ground penetration and no tools, dramatically reducing costs and enhancing project flexibility.

Length	37"/935mm		
Width	26"/650mm		
Height	26"/650mm		
Weight (empty)	15lbs/6.9kg		
Tilt Angle	25°		
TO STATE OF THE PARTY OF THE PA			











PowerRack 1000™

PROPERTIES & INSTALLATION

Unit	One piece rack with two clips	
Material	High Density Polyethylene (HDPE)	
Compatible Modules	All framed modules of overall width between 38.6"/980mm - 41.3"/1050mm	
Module Orientation	Landscape	
Ballast Material	Aggregate gravel, sand, dirt	
Wind Load	120mph ASCE 7-22	
Snow Load	110 psf/5,267 Pa	
Warranty	25 Years	
Certification	UL 2703 Compliant	
Disposal	Reusable and Recyclable	



Ballast Depth at Center of Rack	Volume in Cubic Yards	Weight in Lbs. of Gravel	Weight in Lbs. of Dirt	Weight in Lbs. of Sand
7"	0.065	190 lbs.	170 lbs.	180 lbs.
10″	0.097	285 lbs.	250 lbs.	270 lbs.
11″	0.113	330 lbs.	290 lbs.	315 lbs.
13″	0.129	380 lbs.	335 lbs.	360 lbs.
14"	0.145	425 lbs.	375 lbs.	405 lbs.

*Ballast weights are only intended as a guide. Actual ballast weight requirement depends on project-specific site and wind calculations.

